



SPECIFICATION SHEET

33-VRX180



G-TEK® VR-X™ NYLON GLOVE WITH POLYURETHANE COATING – TOUCHSCREEN COMPATIBLE

- Nylon blended shell, featuring an ultra-thin 18 gauge liner for exceptional dexterity
- VR-X™ Polyurethane coating on full hand provides advanced barrier protection against micro-organism risks, the treated coating provides a tactile grip in wet, dry and slightly oily conditions
- 4.0 AQL, similar to the AQL levels for industrial grade disposable gloves
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Silicone Free
- Washable, resistant to water and ultraviolet light
- Recommended wash cycle: Maximum 6 cycles

APPLICATIONS

- Inspection
- Construction
- Maintenance and Repair
- Manufacturing
- Precision Assembly
- Shipping and Packaging
- Small Parts Handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	Nylon / Treated Polyurethane coating on full hand					
CONSTRUCTION	18 Gauge seamless knit					
COLOR	Shell: ■ Blue / Coating: ■ Black					
SIZES	XS - XXL					
PACKAGING	1 pair per bag, 12 pairs per dozen, 12 dozen per case					
CASE DIMENSIONS	15" x 12.2" x 10.6" / 38cm x 31cm x 27cm					
CASE WEIGHT	XS	S	M	L	XL	XXL
	8.4 lbs 3.8 kg	8.8 lbs 4 kg	9.5 lbs 4.3 kg	10.1 lbs 4.6 kg	11 lbs 5kg	11.9 lbs 5.4kg
COO	China					

PERFORMANCE PROPERTIES

EN388: 3111X						
ABRASION	0	1	2	3	4	-
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
ISO EN374-2	Test method for determining the penetration resistance of gloves that protect against dangerous chemicals and/or micro-organisms					
ISO EN374-5	Performance testing and terminology to determine protection against micro-organisms risks					
ISO 21702:2019	Test method for antiviral activity on non-porous products					
ISO 20743:2013	Specifies quantitative test methods to determine the antibacterial activity of all antibacterial textile products including nonwovens.					
CE CAT III	Suitable for potentially fatal risks					




BARCODES

ITEM	PAIR	PACK	CASE
■ 33-VRX180/XS	616314373398	10616314373395	20616314373392
■ 33-VRX180/S	616314373411	10616314373418	20616314373415
■ 33-VRX180/M	616314373435	10616314373432	20616314373439
■ 33-VRX180/L	616314373459	10616314373456	20616314373453
■ 33-VRX180/XL	616314373480	10616314373487	20616314373484
■ 33-VRX180/XXL	616314373534	10616314373531	20616314373538

DIMENSIONS (in/cm)

	XS	S	M	L	XL	XXL
A	9 / 23	9.4 / 24	9.8 / 25	10.2 / 26	10.4 / 26.5	10.6 / 27
B	3.5 / 9	3.7 / 9.5	3.9 / 10	4.1 / 10.5	4.3 / 11	4.5 / 11.5
H	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.